

Seat Belt for Forklifts

Seat Belt for Forklift - Described in the Regulation guidelines are the use of operative restraints and seatbelts on lift trucks. It says that the accountability falls on the employers' to make sure that each and every machine, piece of equipment and device is used correctly according to the directions of the manufacturer.

Rough Terrain lift trucks have to meet the regulations of ANSI Standard ASME B56.6-1992 with regards to their fabrication, use, design, maintenance and inspection.

Mobile machines like for example side boom tractors with a Rollover Protective Structure (ROPS), have to have seat belts which meet the Society of Automotive Engineers safety requirements; Society of Automotive Engineers Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If whichever mobile equipment has seat belts required by law, the operator and subsequent passengers need to make certain they make use of the belts whenever the motor vehicle is in motion or engaged in operation since this could cause the machine to become unsteady and hence, unsafe.

When a seat belt or other operator restraint is needed on a lift truck.

While working a lift truck, the seat belt requirements would depend on some factors. Contributing factors to this determination may include whether or not the the forklift is outfitted along with a Rollover Protective Structure, the kind of lift truck itself and the year the forklift was actually made. The manufacturer's instructions and the requirements of the applicable standard are referenced in the Regulation.

With regards to powered industrial forklifts, ANSI Standard ASME B56.1-1993 refers to an operator restraint device, system, or enclosure. An operator restraint device, enclosure or system is designed so as to assist the operator in lessening the probability of entrapment of the torso and/or head between the truck and the ground in the event of a tip over. The system or restraint device might comprise a seat belt, even though a seat belt is not essentially a part of such equipment or system.